





THE GARDEN PROFESSIONAL

There's no progress without motion – this applies to us and to many sectors. With the WORK body, we have developed a platform with functional options and we offer a solution that allows for efficient work processes within local authorities, clubs, landscape maintenance, parks, building complexes and much more besides.

From professionals. For professionals.

Your secure equipment storage.







TECHNICAL SPECIFICATIONS (WORK)

Electric motor Valeo Cyclee Go7 Continuous rated power 250 W* Torque 130 Nm Gearshift 7-speed automatic transmission Max. electrically assisted speed 25 km/h* Electric reverse manoeuvring aid yes, up to 6 km/h Electric reverse manoeuvring aid yes, up to 6 km/h Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) 2,770 mm × 995 mm** x 1,990 mm*** Wheelbase 1,746 mm Rear body Work Truck bed, Work (L × W) 1,270 mm × 907 mm (not incl. equipment box, width between wheel houses = 804 mm) Height, end wall / left and right side walls 300 mm / 960 mm Dimensions, opening, rear loading space 830 mm x 1,490 mm Dimensions, equipment box (L × W × H) 300 mm x 907 mm x 340 mm Rear payload up to 200 kg Turning circle 5,500 mm Rechargeable battery slots Replaceable battery system with 2 slots (lockable) Rechargeable battery capacity (per battery) 1,24 kWh (lithium-ion rechargeable battery, 48 V) Charger 230 V / 4 A Range with 1 rechargeable battery up to 50 km Display up to 50 km Display 1,9 inch Suspension Double wishbone axles at front and rear with spring suspension strut and stabiliser bars with spring suspension strut and stabiliser bars with spring suspension strut and stabiliser bars Wheels and Tyres 16° performance wheels with motorbike tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake yes Weather protection priver's cab Coating, front screen yes, with lotus effect Wing mirrors 2x Rear lights 2x Rear lights 2x Rear lights 2x Rear lights 2x with integrated brake light Reflector package yes Height- and tilt-adjustable saddle yes, with folding lid (lockable) Electric required protection foot first and right and right yes, folds back Special body equipment 2 lashing eyes on fixed aluminium front wall Licence required protection for the protection of the privary of the protection of the protec	Vehicle category	Pedelec
Gearshift 7-speed automatic transmission Max. electrically assisted speed 25 km/h* Electric reverse manoeuvring aid yes, up to 6 km/h Electric reverse manoeuvring aid yes, up to 6 km/h Electric starting aid (pushing aid) yes, up to 6 km/h Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) 2,770 mm x 995 mm** x 1,990 mm*** Wheelbase 1,746 mm Rear body Work Truck bed, Work (L × W) 1,270 mm x 907 mm (not incl. equipment box, width between wheel houses = 804 mm) Height, end wall / left and right side walls 300 mm / 960 mm Dimensions, opening, rear loading space 830 mm x 1,490 mm Dimensions, equipment box (L × W × H) 300 mm x 907 mm x 340 mm Rear payload up to 200 kg Turning circle 5,500 mm Rechargeable battery slots Replaceable battery system with 2 slots (lockable) Rechargeable battery capacity (per battery) 1,24 kWh (lithium-ion rechargeable battery, 48 V) Charger 230 V / 4 A Range with 1 rechargeable battery up to 500 km Display 1,9 inch Display 1,9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres 16° performance wheels with motorbike tyres Parking brake yes Weather protection Driver's cab Coating, front screen yes, with lotus effect Wing mirrors 2x Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package yes Indicators yes, with folding lid (lockable) Removable aluminium side walls yes, folds back Special body equipment to X Lashing eyes on fixed aluminium front wall		Valeo Cyclee Go7
Gearshift 7-speed automatic transmission Max. electrically assisted speed 25 km/h* Electric reverse manoeuvring aid yes, up to 6 km/h Electric reverse manoeuvring aid yes, up to 6 km/h Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) 2,770 mm x 995 mm** x 1,990 mm**** Wheelbase 1,746 mm Rear body Work Truck bed, Work (L × W) 1,270 mm x 907 mm (not incl. equipment box, width between wheel houses = 804 mm) Height, end wall / left and right side walls 300 mm / 960 mm Dimensions, opening, rear loading space 830 mm x 1,490 mm Dimensions, equipment box (L × W × H) 300 mm x 907 mm x 340 mm Rear payload up to 200 kg Turning circle 5,500 mm Rechargeable battery slots Replaceable battery system with 2 slots (lockable) Rechargeable battery capacity (per battery) 1,24 kWh (lithium-ion rechargeable battery, 48 V) Charger 230 V / 4 A Range with 1 rechargeable battery up to 50 km Display 1,9 inch Suspension Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres 16° performance wheels with motorbike tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake yes Weather protection Driver's cab Coating, front screen yes, with lotus effect Wing mirrors 2x Rear lights 2x with integrated brake light Reflector package yes Indicators yes Lockable equipment box yes, left and right Felding rear wall Special body equipment Special body equipm	Continuous rated power	250 W*
Max. electrically assisted speed 25 km/h* Electric reverse manoeuvring aid yes, up to 6 km/h	Torque	130 Nm
Electric reverse manoeuvring aid Electric starting aid (pushing aid) Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) Wheelbase 1,746 mm Rear body Truck bed, Work (L × W) Height, end wall / left and right side walls Dimensions, opening, rear loading space Dimensions, opening, rear loading space Dimensions, equipment box (L × W × H) Rear payload Up to 200 kg Turning circle S,500 mm Rechargeable battery slots Rechargeable battery capacity (per battery) Display 1.24 kWh (lithium-ion rechargeable battery, 48 V) Charger Braking system Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Doriver's cab Weather protection Coating, front screen Wing mirrors Electric starting aid (push load) Parking brake Westher protection Coating, front screen Wing mirrors Recar lights Reflector package Indicators Removable aluminium side walls yes, left and right Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall Special body equipment Psys to 6 km/h Son kg External dimensions, vehicle (L × W × H) Roys with folding lid (lockable) Recar bardy Rear by Smith olders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Gearshift	7-speed automatic transmission
Electric reverse manoeuvring aid Electric starting aid (pushing aid) Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) Wheelbase 1,746 mm Rear body Truck bed, Work (L × W) Height, end wall / left and right side walls Dimensions, opening, rear loading space Dimensions, opening, rear loading space Dimensions, equipment box (L × W × H) Rear payload Up to 200 kg Turning circle S,500 mm Rechargeable battery slots Rechargeable battery capacity (per battery) Display 1.24 kWh (lithium-ion rechargeable battery, 48 V) Charger Braking system Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Doriver's cab Weather protection Coating, front screen Wing mirrors Electric starting aid (push load) Parking brake Westher protection Coating, front screen Wing mirrors Recar lights Reflector package Indicators Removable aluminium side walls yes, left and right Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall Special body equipment Psys to 6 km/h Son kg External dimensions, vehicle (L × W × H) Roys with folding lid (lockable) Recar bardy Rear by Smith olders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Max. electrically assisted speed	
Gross vehicle weight 500 kg External dimensions, vehicle (L × W × H) 2,770 mm x 995 mm** x 1,990 mm*** Wheelbase 1,746 mm Rear body Work Truck bed, Work (L × W) 1,270 mm x 997 mm (not incl. equipment box, width between wheel houses = 804 mm) Height, end wall / left and right side walls 300 mm / 960 mm Dimensions, opening, rear loading space 830 mm x 1,490 mm Dimensions, equipment box (L × W × H) 300 mm x 907 mm x 340 mm Rear payload up to 200 kg Turning circle 5,500 mm Rechargeable battery slots Replaceable battery system with 2 slots (lockable) Rechargeable battery capacity (per battery) 1,24 kWh (lithium-ion rechargeable battery, 48 V) Charger 230 V / 4 A Range with 1 rechargeable battery up to 50 km Display 1,9 inch Suspension 20 buble wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres 16° performance wheels with motorbike tyres Hydraulic disc brakes on all 4 wheels Parking brake yes Weather protection Driver's cab Coating, front screen yes, with lotus effect Wing mirrors 2x Rear lights 2x with integrated brake light Reflector package Indicators yes Indicators yes, with folding lid (lockable) Removable aluminium side walls yes, folds back Removable aluminium side walls yes, solfixed aluminium front wall	Electric reverse manoeuvring aid	yes, up to 6 km/h
External dimensions, vehicle (L × W × H) Wheelbase Rear body Truck bed, Work (L × W) Height, end wall / left and right side walls Dimensions, opening, rear loading space Dimensions, equipment box (L × W × H) Rear payload Turning circle Rechargeable battery slots Rechargeable battery capacity (per battery) Display Display Display Load Tyres Braking system Wheels and Tyres Braking system Weather protection Coating, front screen Wing mirrors Bells Lx Rear loading front screen Wing mirrors Reflector package Indicators Height- and tilt-adjustable saddle Special body equipment D, 1,2770 mm x 995 mm** x 1,990 mm** 1,2740 mm x 997 mm (not incl. equipment box, width between wheel houses = 804 mm) 1,2700 mm x 997 mm x 997 mm (not incl. equipment box, width box, width between wheel houses = 804 mm) Height, end wall / left and right side walls 300 mm x 907 mm x 340 mm 1,900 mm 2900 kg 1,900 kg 1,24 kWh (lithium-ion rechargeable battery, 48 V) 230 V / 4 A 24 Particular disc battery system with 2 slots (lockable) 1.9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars With spring suspension strut and stabiliser bars Wheels and Tyres 16" performance wheels with motorbike tyres Hydraulic disc brakes on all 4 wheels Parking brake Yes Weather protection Driver's cab yes, with lotus effect Wing mirrors 2 x Bells 1 x Headlights 2 x Rear lights Qyes, with integrated brake light yes, folds back Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Electric starting aid (pushing aid)	yes, up to 6 km/h
Neelbase 1,746 mm Nork	Gross vehicle weight	500 kg
Rear body Truck bed, Work (L × W) Height, end wall / left and right side walls Dimensions, opening, rear loading space 830 mm x 1,490 mm Dimensions, equipment box (L × W × H) Rear payload Turning circle S-500 mm Rechargeable battery slots Rechargeable battery slots Rechargeable battery capacity (per battery) Charger 230 V / 4 A Range with 1 rechargeable battery Display 1.9 inch Suspension Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors Bells Headlights 2x Rear lights Reflector package Indicators Height- and tilt-adjustable saddle pesson listed and right yes, with folding lid (lockable) ges, bolds back Pesson lized brake aluminium front wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	External dimensions, vehicle (L × W × H)	2,770 mm x 995 mm** x 1,990 mm***
Truck bed, Work (L × W) Height, end wall / left and right side walls Dimensions, opening, rear loading space Dimensions, equipment box (L × W × H) Rear payload Turning circle Rechargeable battery slots Rechargeable battery capacity (per battery) Charger Ange with 1 rechargeable battery Display Display Display Display Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors Bells 1x Headlights Recar lights Rechargeable saddle Lockable equipment box Wes with folding lid (lockable) 2x with integrated brake light Reflector package Indicators Rechargeable saddle Lockable equipment box Rechargeable battery 1.270 mm x 907 mm (not incl. equipment box, width between wheel houses = 804 mm) 300 mm / 960 mm 300 mm / 960 mm 300 mm x 907 mm x 907 mm x 907 mm 300 mm x 907 mm x 340 mm up to 200 kg Replaccable battery system with 2 slots (lockable) 1.24 kWh (lithium-ion rechargeable battery, 48 V) 1.24 kWh (lithium-ion rechargeable battery, 48 V) 230 V / 4 A 230 V / 4 A 210 V	Wheelbase	1,746 mm
Height, end wall / left and right side walls Dimensions, opening, rear loading space Biomensions, equipment box (L × W × H) Rear payload Turning circle Rechargeable battery slots Rechargeable battery capacity (per battery) Charger Range with 1 rechargeable battery Display Display Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors Bells Headlights Rear lights Reflector package Indicators Removable aluminium side walls Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Rear body	Work
Dimensions, opening, rear loading space Dimensions, equipment box (L × W × H) Dimensions, equipment box (L × W × H) Rear payload Up to 200 kg Turning circle S,500 mm Replaceable battery system with 2 slots (lockable) Rechargeable battery capacity (per battery) L24 kWh (lithium-ion rechargeable battery, 48 V) Charger 230 V / 4 A Range with 1 rechargeable battery Up to 50 km Display Display Display Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Yes Weather protection Driver's cab Coating, front screen Wing mirrors Parking front screen Wing mirrors Suspension Yes, with lotus effect Wing mirrors Yes, with lotus effect Wing mirrors Yes, with integrated brake light Reflector package Indicators Headlights Yes Height- and tilt-adjustable saddle Lockable equipment box Yes, with folding lid (lockable) Yes, left and right Yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Truck bed, Work (L × W)	
Dimensions, equipment box (L × W × H) Rear payload Turning circle Rechargeable battery slots Rechargeable battery capacity (per battery) Charger Range with 1 rechargeable battery Display Display Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Wing mirrors Bells Headlights 2x Rear lights Reflector package Indicators Reixer a type in the suspension Bound mm x 907 mm x 340 mm up to 200 kg Spond mm x 907 mm x 340 mm x 907 mm x 340 mm up to 200 kg Spond mm x 907 mm x 340 mm x 907 mm x 340 mm up to 200 kg Replaceable battery system with 2 slots (lockable) 1.24 kWh (lithium-ion rechargeable battery, 48 V) 2.04 kWh (lithium-ion rechargeable battery, 48 V) 2.05 km 2.09 inch 2.09 up to 50 km 2.09 inch 2.00 up to 50 km 2.00 up	Height, end wall / left and right side walls	300 mm / 960 mm
Rear payload Turning circle S,500 mm Rechargeable battery slots Rechargeable battery capacity (per battery) Charger Range with 1 rechargeable battery Display Display Duble wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors Ells Headlights Rear lights Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment Lockable equipment Lockable equipment Axes with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Yes Weather protection Driver's cab Ves, with lotus effect Ving mirrors Lax Rear lights Lockable equipment box Lockable equipment Ves, with folding lid (lockable) Ves, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Dimensions, opening, rear loading space	830 mm x 1,490 mm
Turning circle Rechargeable battery slots Rechargeable battery capacity (per battery) Charger Range with 1 rechargeable battery Display Suspension Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Weather protection Coating, front screen Wing mirrors Bells Headlights Rear lights Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment Sysen illows a Replaceable battery yes, with folding lid (lockable) Person with 2 slots (lockable) 1.24 kWh (lithium-ion rechargeable battery, 48 V) 1.24 kWh (lithium-ion rechargeable battery 1.24 kWh (lithi	Dimensions, equipment box (L × W × H)	300 mm x 907 mm x 340 mm
Rechargeable battery slotsReplaceable battery system with 2 slots (lockable)Rechargeable battery capacity (per battery)1.24 kWh (lithium-ion rechargeable battery, 48 V)Charger230 V / 4 ARange with 1 rechargeable batteryup to 50 kmDisplay1.9 inchSuspensionDouble wishbone axles at front and rear with spring suspension strut and stabiliser barsWheels and Tyres16" performance wheels with motorbike tyresBraking systemHydraulic disc brakes on all 4 wheelsParking brakeyesWeather protectionDriver's cabCoating, front screenyes, with lotus effectWing mirrors2xBells1xHeadlights2xRear lights2x with integrated brake lightReflector packageyesIndicatorsyesHeight- and tilt-adjustable saddleyesLockable equipment boxyes, with folding lid (lockable)Removable aluminium side wallsyes, left and rightFolding rear wallyes, folds backSpecial body equipmentAssembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Rear payload	up to 200 kg
Rechargeable battery capacity (per battery) Charger 230 V / 4 A Range with 1 rechargeable battery Display 1.9 inch Suspension Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x Rear lights Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment 1.24 kWh (lithium-ion rechargeable battery, 48 V) 230 V / 4 A 24 kWh (lithium-ion rechargeable battery, 48 V) 250 V / 4 A 260	Turning circle	5,500 mm
Charger Range with 1 rechargeable battery Display 1.9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres 16" performance wheels with motorbike tyres Braking system Hydraulic disc brakes on all 4 wheels yes Weather protection Driver's cab Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment 230 V / 4 A up to 50 km up to 50 km Log Nom 1.9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars 1.9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars 16" performance wheels with motorbike tyres Hydraulic disc brakes on all 4 wheels yes Weather protection Driver's cab 2x 2x Real lights 2x Rear lights 2x Rear lights 2x with integrated brake light yes Indicators yes Indicators yes Indicators yes Indicators Yes Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Rechargeable battery slots	Replaceable battery system with 2 slots (lockable)
Range with 1 rechargeable battery Display 1.9 inch Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Wheels and Tyres 16" performance wheels with motorbike tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Driver's cab Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Rechargeable battery capacity (per battery)	1.24 kWh (lithium-ion rechargeable battery, 48 V)
Display1.9 inchSuspensionDouble wishbone axles at front and rear with spring suspension strut and stabiliser barsWheels and Tyres16" performance wheels with motorbike tyresBraking systemHydraulic disc brakes on all 4 wheelsParking brakeyesWeather protectionDriver's cabCoating, front screenyes, with lotus effectWing mirrors2xBells1xHeadlights2x with integrated brake lightRear lights2x with integrated brake lightReflector packageyesIndicatorsyesHeight- and tilt-adjustable saddleyesLockable equipment boxyes, with folding lid (lockable)Removable aluminium side wallsyes, left and rightFolding rear wallyes, folds backSpecial body equipmentAssembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Charger	230 V / 4 A
Suspension Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Coating, front screen Wing mirrors Earlights Rear lights Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Double wishbone axles at front and rear with spring suspension strut and stabiliser bars Double wishbone axles at front and rear with spring suspension strut and stabiliser bars 16" performance wheels with motorbike tyres Hydraulic disc brakes on all 4 wheels yes Lot able spring suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels yes Lot able spring suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking suspension strut and stabiliser bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars Hydraulic disc brakes on all 4 wheels Parking bars	Range with 1 rechargeable battery	up to 50 km
Wheels and Tyres 16" performance wheels with motorbike tyres Braking system Hydraulic disc brakes on all 4 wheels Parking brake Weather protection Driver's cab Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment 26" performance wheels with motorbike tyres Hydraulic disc brakes on all 4 wheels yes Loture of the protection Driver's cab 2x 2x 2x 2x Rear lights 2x Rear lights 2yes Indicators yes Height- and tilt-adjustable saddle yes Lockable equipment box Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Display	1.9 inch
Braking system Parking brake Weather protection Driver's cab Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Suspension	
Parking brake Weather protection Coating, front screen Wing mirrors Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Parking brake yes Uriver's cab 2x 2x 2x 2x 3x 4x 4x 4x 4x 4x 4x 4x 4x 4	Wheels and Tyres	16" performance wheels with motorbike tyres
Weather protectionDriver's cabCoating, front screenyes, with lotus effectWing mirrors2xBells1xHeadlights2xRear lights2x with integrated brake lightReflector packageyesIndicatorsyesHeight- and tilt-adjustable saddleyesLockable equipment boxyes, with folding lid (lockable)Removable aluminium side wallsyes, left and rightFolding rear wallyes, folds backSpecial body equipmentAssembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Braking system	Hydraulic disc brakes on all 4 wheels
Coating, front screen Wing mirrors 2x Bells 1x Headlights 2x with integrated brake light Reflector package Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment yes, with folding lid (lockable) Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Parking brake	<u>yes</u>
Wing mirrors2xBells1xHeadlights2xRear lights2x with integrated brake lightReflector packageyesIndicatorsyesHeight- and tilt-adjustable saddleyesLockable equipment boxyes, with folding lid (lockable)Removable aluminium side wallsyes, left and rightFolding rear wallyes, folds backSpecial body equipmentAssembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Weather protection	Driver's cab
Bells 1x Headlights 2x Rear lights 2x with integrated brake light Reflector package yes Indicators yes Height- and tilt-adjustable saddle yes Lockable equipment box yes, with folding lid (lockable) Removable aluminium side walls yes, left and right Folding rear wall yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Coating, front screen	yes, with lotus effect
Headlights 2x Rear lights 2x with integrated brake light Reflector package yes Indicators yes Height- and tilt-adjustable saddle yes Lockable equipment box yes, with folding lid (lockable) Removable aluminium side walls yes, left and right Folding rear wall yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Wing mirrors	2x
Rear lights 2x with integrated brake light Reflector package yes Indicators yes Height- and tilt-adjustable saddle yes Lockable equipment box yes, with folding lid (lockable) Removable aluminium side walls yes, left and right Folding rear wall yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Bells	1x
Reflector package Indicators yes Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Headlights	<u>2x</u>
Indicators Height- and tilt-adjustable saddle Lockable equipment box Removable aluminium side walls Folding rear wall Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Rear lights	2x with integrated brake light
Height- and tilt-adjustable saddle Lockable equipment box yes, with folding lid (lockable) Removable aluminium side walls Folding rear wall yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Reflector package	<u>yes</u>
Lockable equipment boxyes, with folding lid (lockable)Removable aluminium side wallsyes, left and rightFolding rear wallyes, folds backSpecial body equipmentAssembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Indicators	<u>yes</u>
Removable aluminium side walls Folding rear wall Special body equipment yes, left and right yes, folds back Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Height- and tilt-adjustable saddle	yes
Folding rear wall yes, folds back Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Lockable equipment box	yes, with folding lid (lockable)
Special body equipment Assembly set: 4 device holders, 1 Greifboy holder, 2 lashing eyes on fixed aluminium front wall	Removable aluminium side walls	yes, left and right
2 lashing eyes on fixed aluminium front wall	Folding rear wall	
Licence required no*	Special body equipment	
	Licence required	no*

In spite of the technical data being subjected to extensive checks, we cannot rule out errors and we assume no liability for the content. All dimensions are approximate. *Subject to national legislation. The European Union has a max. continuous rated power limit of 250 W. Continuous rated power represents a system's maximum effective output generated by the motors over a period of 30 minutes without the temperature rising above a specified value. The maximum – temporary – peak output of pedelecs may exceed this. The use of cycle paths is permitted in most EU countries. The national laws as amended apply ** Not incl. mirror *** Vehicle height incl. optional weather protection and without tool holders